

Appendix A

Explanations and Examples of construct of the ORM Grammar

`<REMARK-SPEC> ::= REM [<any remarks>]`

Explanation: Any line starting with REM is considered a remark (comment) line and it is ignored.

Example: REM This is a comment

`<ORM-INFO> ::= [;ORMId=<ORMId>] [;ORMFile=<fileName>]`

Explanation: `<ORMId>` specifies the Object Relational Mapping id of a specification. The default `<ORMId>` is the string "defaultORMId". The Object-Relational Mapping information (metadata) stored in the database corresponding to the given `<ORMId>` is used for subsequent processing.

An ORMFile specification overrides the mapping information corresponding to `<ORMId>`. This is an easy way to experiment with different mappings before storing that information permanently in the database.

Example: See `<DATABASE-URL>` below.

`<DATABASE-URL> ::= <regularURL> [<ORM-INFO>]`

1 **Explanation:** <DATABASE-URL> consists of the url (uniform resource
2 locator, which includes database name, user name and
3 password among other things) of the database to be
4 connected to, optionally followed by ORM specific
5 information <ORM_INFO>. <ORM_INFO> is used to
6 initialize the database with the Object-Relational
7 Mapping information or to retrieve the Object-
8 Relational Mapping information from the database.

9 **Example:** See <DATABASE-SPEC> below.

10

11

12 <ENDDATABASE-SPEC> ::= ;

13 **Explanation:** This is just a delimiter to signify the end of

14 <DATABASE-SPEC>

15

16 <DATABASE-SPEC> ::= DATABASE <DATABASE-URL>

17 <ENDDATABASE-SPEC>

18 **Explanation:** A <DATABASE-SPEC> specifies the database and the

19 Object-Relational Mapping (metadata) information to

20 be used. Please see <DATABASE-URL> above for more

21 details.

22 **Example:** DATABASE jdbc:odbc:sqlpubs; user=guest; password=hello;

23 ORMId=pubs01;

1 or

2 DATABASE jdbc:odbc:sqlpubs; user=guest; password=hello;

3 ORMFile=pubs.jdx;

4 The first example specifies the use of Object-

5 Relational Mapping information stored in the database

6 corresponding to the ORMId "pubs01"

7 The second example specifies that the Object-

8 Relational Mapping information should be retrieved from

9 the file pubs. jdx

10

11 <PRIMARY-KEY-SPEC> ::= PRIMARY_KEY {<attribName> . . . }

12 **Explanation:** A <PRIMARY-KEY-SPEC> identifies the attribute names

13 whose combined values uniquely identify a particular

14 object. For a collection object, it specifies the

15 attributes whose values are the same for all the

16 objects in the collection.

17 **Example:** PRIMARY_KEY pub_id

18 or

19 PRIMARY_KEY title_id lorange

20

21 <REFERENCE-KEY-SPEC> ::= REFERENCE_KEY <referenceKeyName>

22 {<attribName> . . . }

1 Explanation: A <REFERENCE-KEY-SPEC> identifies the attribute
2 names whose combined values uniquely identify a
3 particular object. This may be an alternate way of
4 identifying objects of a particular class.
5 <REFERENCE-KEY-SPEC> is not allowed for collection
6 classes.

7 Example: REFERENCE_KEY name fname minit lname
8 Here we are defining a reference key "name" consisting
9 of three attributes - fname, minit and lname.

10

11 <SQLMAP-SPEC> ::= SQLMAP FOR <attribName>

12 [COLUMN_NAME <columnName>]

13 [SQLTYPE <sqlType>]

14 [NULLABLE]

15 Explanation: Through <SQLMAP-SPEC>, one can refine the mapping of
16 a class attribute to SQL column in one of the
17 following ways - use a column name different than the
18 attribute name, use an SQL data type different than
19 the default SQL data type for the attribute type,
20 allow the column to be nullable. Allowing mapping
21 of an attribute name to a different column name may
22 be handy if the existing column name is cryptic and
23 we want a more meaningful attribute name at the class

definition level. Semantic knowledge of the data may be used to improve the storage efficiency for an attribute by specifying a more refined SQL type. For example, a String attribute (zipCode) may be mapped to varchar(10) instead of default varchar(255).

Some object-oriented languages like Java provide facility of reflection whereby the attribute names for a class and their types may be determined programmatically. If that is not the case, then a <SQLMAP-SPEC> needs to be specified for each attribute. Otherwise, some default mapping may be done using reflection facility.

Example: SQLMAP FOR prInfo COLUMN_NAME pr_info SQLTYPE text

or

SQLMAP FOR zip SQLTYPE varchar(10)

```
<RELATIONSHIP-SPEC> ::= RELATIONSHIP <attribName>
                           REFERENCES <targetClassName>
                           { EMBEDDED | [BYVALUE] [REFERENCED_KEY
                           <referencedKeyName>] WITH<attribName> . . . }
```

Explanation: <RELATIONSHIP-SPEC> is used to provide details for a complex attribute.

1 EMBEDDED keyword means that the value of a complex
2 attribute is embedded in a large binary column of the
3 same table where rest of the primitive attributes are
4 stored. This may be an optimized way for storing a
5 referenced object if that referenced object does not
6 need to be retrieved in any other context.

7 A Non-embedded complex attribute references a regular
8 class or a collection class identified by
9 <targetClassName>.

10 BYVALUE keyword implies that the referenced object
11 (may be a collection object) does not have an
12 independent existence without the existence of the
13 containing object. When a containing object is
14 stored, all the objects referenced through its
15 BYVALUE complex attributes are also stored in the
16 database. If a containing object is deleted, its
17 BYVALUE referenced objects should also be deleted.

18 <referenceKeyName> specifies the name of a reference
19 key of the class <targetClassName>. By default,
20 referencing is done to the PrimaryKey of the target
21 class.

22 The list of <attribName> is an ordered enumeration of
23 the source attributes in the current class which are

1 used to find the target class objects through the
2 reference key. The data types of the source
3 attributes should be compatible with the data types
4 of the attributes defining the reference key in the
5 target class.

6 Example: RELATIONSHIP titles REFERENCES ArrayTitle BYVALUE WITH
7 pub_id

8 or

9 RELATIONSHIP job REFERENCES Job REFERENCED_KEY
10 PrimaryKey WITH job_id

11 The first specification means that the complex
12 attribute 'titles' references an object of type
13 ArrayTitle (which is a collection (array) of Title
14 objects). The referenced object is contained in the
15 current object by value. The attribute pub_id of
16 the containing class is used to identify the (default
17 primary key of the) referencing object.

18 The second example specifies that the complex
19 attribute 'job' references an object of class 'Job'
20 with the referencing object's attribute 'job_id' which
21 should match the primary key attribute of the class
22 'Job'.

1 <ENDCLASS-SPEC> ::= ;

2 **Explanation:** This is just a delimiter to signify the end of a
3 <CLASS-SPEC> or a <COLLECTION-CLASS-SPEC>.

4
5 <CLASS-SPEC> ::= CLASS<className>[TABLE<tableName>]<PRIMARY-KEY-SPEC>
6 [7 [8 [9 <ENDCLASS-SPEC>

10 **Explanation:** A <CLASS-SPEC> encapsulates all the Object-
11 Relational Mapping information about one class.
12 The <tableName> specifies the name of the relational
13 table which holds the instances of this class. The
14 default <tableName> is the same as the <className>.
15 Other specifications have been explained earlier.
16 Please note that it is mandatory to specify <PRIMARY-
17 KEY-SPEC> for a class.

18 **Example:** CLASS Title TABLE titles
19 PRIMARY_KEY title_id
20 RELATIONSHIP royscheds REFERENCES ArrayRoySched
21 BYVALUE WITH
22 title_id
23 SQLMAP FOR price SQLTYPE Money

1 ;

2

3 <ORDERBY-SPEC> ::= ORDERBY {<attribName> . . . }

4 **Explanation:** An <ORDERBY-SPEC> of a <COLLECTION-CLASS-SPEC>

5 specifies an ordered list of attributes whose values

6 are used to sequence the objects in a collection

7 during retrieval.

8 **Example:** ORDERBY ytd_sales title_id

9 The above specification for the collection class

10 ArrayTitle means that such a collection of objects (e.

11 g. in the titles attribute of a Publisher class

12 object) should be ordered as per the values of

13 ytd_sales and title_id attributes of the Title objects

14 in the collection.

15

16 <COLLECTION-CLASS-SPEC> ::= COLLECTION_CLASS <className>

17 COLLECTION_TYPE {ARRAY | VECTOR}

18 ELEMENT_CLASS <elementClassName>

19 [ELEMENT_TABLE <elementTableName>]

20 <PRIMARY-KEY-SPEC>

21 [<ORDERBY-SPEC>]

22 <ENDCLASS-SPEC>

1

2 Explanation: A <COLLECTION-CLASS-SPEC> encapsulates all the

3 Object-Relational Mapping information about a
4 collection class. A collection is actually a
5 pseudo-class; there may not be an actual class by
6 that name in the program.

7 The COLLECTION_TYPE specifies how the objects in the
8 collection are combined together - in an array or in
9 a vector.

10 The <elementClassName> specifies the class whose
11 instances form the collection. Even the instances
12 of a subclass of the <elementClassName> class may
13 participate in a collection.

14 The mandatory <PRIMARY-KEY-SPEC> specifies the
15 attributes which are the basis for realizing a
16 collection. The values of these attributes are the
17 same for all the objects in a collection.

18 The <elementTableName> specifies the name of the
19 relational table which holds the instances of the
20 collection objects. The default table is the same
21 as the table for <elementClassName> class.

22 Other specifications have been explained earlier.

```

1  Example:      COLLECTION_CLASS ArrayRoySched COLLECTION_TYPE ARRAY
2
3                  ELEMENT_CLASS
4
5                  RoySched
6
7                  PRIMARY_KEY title_id
8
9                  ORDERBY royalty
10
11                 ;

```

```

8  <ORM-SPEC> ::= <DATABASE-SPEC>

```

```

9
10         Any combination of <CLASS-SPEC>
11
12         <COLLECTION-CLASS-SPEC>,
13
14         <SEQUENCE-SPEC> and <REMARK-SPEC>

```

```

12 Explanation: An Object-Relational Mapping specification <ORM-SPEC>
13
14         consists of <DATABASE-SPEC> followed by any combination
15
16         of <CLASS-SPEC>, <COLLECTION-CLASS-SPEC> and <REMARK-
17
18         SPEC>. This is what an <ORMFile> contains. The
19
20         following example has an ORMId of pubs01.
21
22         This specification is contained in a file (pubs.
23
24         jdx).

```

```

19 Example:      DATABASE
20
21                 jdbc:odbc:sqlpubs;user=guest;password=hello;ORMId=pub
22
23                 s01
24
25                 ;
26
27                 REM

```

```
1      CLASS RoySched TABLE roysched
2      PRIMARY_KEY title_id lorange
3      ;
4      COLLECTION_CLASS ArrayRoySched COLLECTION_TYPE ARRAY
5      ELEMENT_CLASS RoySched
6      PRIMARY_KEY title_id
7      ORDERBY royalty
8      ;
9      CLASS Title TABLE titles
10     PRIMARY_KEY title_id
11     RELATIONSHIP royscheds REFERENCES ArrayRoySched
12     BYVALUE WITH
13         title_id
14     SQLMAP FOR price SQLTYPE Money
15     ;
16     COLLECTION_CLASS ArrayTitle COLLECTION_TYPE ARRAY
17     ELEMENT_CLASS
18         Title
19     PRIMARY_KEY pub_id
20     ORDERBY ytd_sales title_id
21     ;
22     CLASS PubInfo TABLE pub_info
23     PRIMARY_KEY pub_id
```

```
1      SQLMAP FOR logo SQLTYPE image
2      SQLMAP FOR prInfo COLUMN_NAME pr_info SQLTYPE text
3      ;
4      CLASS Publisher TABLE publishers
5      PRIMARY_KEY pub_id
6      RELATIONSHIP pubInfo REFERENCES PubInfo BYVALUE WITH
7      pub_id
8      RELATIONSHIP titles REFERENCES ArrayTitle BYVALUE
9      WITH pub_id
10     ;
11     CLASS Job TABLE jobs
12     PRIMARY_KEY job_id
13     ;
14     CLASS Emp TABLE employee
15     PRIMARY_KEY emp_id
16     RELATIONSHIP job REFERENCES Job REFERENCED_KEY
17     PrimaryKey WITH
18         job_id
19     RELATIONSHIP publisher REFERENCES Publisher WITH
20     pub_id
21     ;
22     CLASS TitlePub
23     PRIMARY_KEY title_id
```

```
1      ;
2      CLASS LinkList TABLE linklist
3      PRIMARY_KEY link_id
4      RELATIONSHIP next REFERENCES LinkList BYVALUE WITH
5      next_link_id
6      ;
```

```
7
8
9  <SEQUENCE-SPEC> ::= SEQUENCE <sequenceName>
10                      MAX_INCREMENT <maxIncrementValue>
11                      [START_WITH <startingVal>]
```

12 **Explanation:** A <SEQUENCE-SPEC> defines a sequencer which can
13 provide chunks of persistently unique sequence
14 numbers.
15 <maxIncrementValue> is used to do sanity-check
16 against requests which may erroneously ask for a
17 large chunk of sequences which may quickly reduce the
18 availability of new sequence numbers.
19 Optional <startVal> specifies the starting sequence
20 number provided through this sequencer. The
21 default is 1.

22
23 **Example:** SEQUENCE seqFoo MAX_INCREMENT 100 or

1 SEQUENCE seqBar MAX_INCREMENT 1000 START_WITH 10001
2 The second sequencer (seqBar) starts with a value of
3 10001.

4